# CATÁLOGO DE PRODUTOS

**GRUPO** 

# enercom REDES ELÉTRICAS SUBTERRÂNEAS

37 ANOS

LINHA COMPLETA DE PRODUTOS PARA REDES ELÉTRICAS SUBTERRÂNEAS













# REDES ELÉTRICAS SUBTERRÂNEAS

# **DESCONECTÁVEIS 200A LOADBREAK**



Os acessórios desconectáveis 200A LOADBREAK oferecem um meio eficaz de conectar e desconectar cabos e equipamentos em sistemas de potência.

Os acessórios LOADBREAK são concebidos para operação (conexão e desconexão) energizada, com bastões do tipo linha viva.

Os componentes podem ser tamponados e isolados com capuzes, plugues e buchas.

A linha LOADBREAK possui também acessórios para aterrar, testar, proteger contra descargas atmosféricas, e fusíveis limitadores de corrente.

Pontos adicionais de conexão podem ser obtidos com o uso de barramentos e plugues by-pass.

Os acessórios Elastimold são 100% testados em fábrica e atendem todos os ensaios da norma ANSI/IEEE 386 e NBR 11835/EB2134 inclusive de compatibilidade total.

# **ESPECIFICAÇÕES**

# Especificações de corrente:

200A operação contínua 10KA simétricos/10 Ciclos

# Especificações de tensão: Classe 15kV

Fase-Terra 8.3kV
Fase-Fase 14.4kV
NBI 95KV
Suporta 34kV AC
Suporta 53kV DC
Tensão de Extinção Descargas
Parciais (Corona) 11kV

# Classe 25kV


Fase-Terra 15.2kV
Fase-Fase 26.3kV
NBI 125kV
Suporta 40kV AC
Suporta 78kV DC
Tensão de Extinção Descargas
Parciais (Corona) 19kV

# Classe 35kV

Fase-Terra 21.1kV
Fase-Fase 36.6kV
NBI 150kV
Suporta 50kV AC
Suporta 103kV DC
Tensão de Extinção Descargas
Parciais (Corona) 26kV

# Componentes desconectáveis Loadbreak 200 AMP

Conexão do cabo ao equipamento







CÓDIGO

15-ETP600 15-LRTP600

# PLUGUE DE REDUÇÃO PR - 15kV-600/200A



The Chardon Elbow Tap Plug (ETP) and Load Reducing Tap Plug (LRTP) are used to convert a standard 600A deadbreak interface to a standard 200A loadbreak interface.

The ETP is ideal for applications where a 200A tap is desired for test or ground purposes. The ETP is also ideal for adding a 200A tap to an existing 600A T-Body connector. The 200A interface allows for live test, visible ground, addition of a 200A tap, or installation of an elbow arrester.

The LRTP is ideal for applications where the termination will be separated to achieve a visible break and ground. Having the T-body and LRTP connected, as one unit, makes it easier to install and remove from the mating bushing interface. The 200A interface allows for live test, phasing,

and visible ground. In addition, it can be used to add a 200A tap, or for the installation of an elbow arrester. The LRTP has a factory installed alignment guide with a shear pin that allows the alignment guide to disengage after installation. When the LRTP is screwed into the threaded insert of a bushing extender or threaded 600/900A compression connector, the alignment guide disengages once the proper amount of torque is applied.

Both the ETP and LRTP meet all the requirements of IEEE Standard 386, and are 200A three phase switching and three phase fault close rated.

The Chardon ETP and LRTP incorporate an all copper current path. This provides reliable and consistent performance under all conditions.

# **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 11 kV
- I AC 1 Minute Withstand 34 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	15 kV	
Max. Rating Phase to Phase	14.4 kV	
Max. Rating Phase to Ground	8.3 kV	
AC 1 Minate Withstand	34 EV	
DC 15 Minute Withstand	53 NV	
BIL and Full Wave Crest	95 BV	
Minimum Corona Voltage Level	11 KV	

# **CURRENT RATINGS**

	Description	Amperes
	Continuous	600 amps ms
600A Interface	Short Time	+ 25,000 amps rms symmetrical for 0.17 s + 10,000 amps rms symmetrical for 3.0 s
200A Interface	Continuous	200 amps ms
	Switching	10 operations at 200 amps rms at 14.4 kV
	Fault Close	10,000 amps rms symmetrical at 14.4 kV for 0.17 s after 10 consecutive successful switching operations
	Short Time	10,000 amps rms symmetrical for 0.17 s     3,500 amps rms symmetrical for 3.0 s

"Note: System design and protection must recognize the ratings of 200A interface.

# DETAILED COMPOSITION OF THE CHARDON ELBOW TAP PLUG (ETP)

#### / LOCKING GROOVE

Locking groove assures proper Installation by 'locking' into elbow.

#### # ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

#### # FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### I SEMICONDUCTING SHIELD

Precision molded peroxide cured semiconducting shield provides ground shield continuity and meets the requirements of IEEE Standard 592.

#### # HEX BROACH

5/16" hex broach permits installation with torque tool.

600A INTERFACE

# 200A INTERFACE



#### ISTOP RING

Limits piston and finger contact travel during fault close.

#### I DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector sheld.

### INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated in-house for complete control of subber characteristics.

# I THREADED CONNECTION TO T-BODY

5/8" – 11 UNC copper threads provided connection to T-Body connector.

# DETAILED COMPOSITION OF THE CHARDON LOAD REDUCING TAP PLUG (LRTP)

#### /LOCKING GROOVE

Locking groove assures proper installation by "locking" into elbow.

#### # ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

#### # FINGER CONTACT

Tim plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / SEMICONDUCTING SHIELD

Precision molded peroxide cured semiconducting shield provides ground shield continuity and meets the requirements of IEEE Standard 592.

### / THREADED CONNECTION TO T-BODY

5/8" – 11 UNC threads provided connection to T-Body connector.

ORDERING INFORMATION



Limits piston and finger contact travel during fault close.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated inhouse for complete control of rubber characteristics.

#### #HEX BROACH

5/16" hex broadh permits installation with torque tool.

### ▼ THREADED CONNECTION TO T-BODY

15/16" – 9 NS 2A stationary threads mate with 600A compression connector or bushing extender.

600A INTERFACE

15 kV, 600A Load Reducing Tap Plug

15-LRTP600

# ORDERING INFORMATION

15 kV, 600A Elbow Tap Plug

15-ETP600





CÓDIGO 15-LBI200

# PLUGUE DE INSERÇÃO SIMPLES PIS - 15kV-200A



The Chardon Bushing Insert threads onto a standard 200A bushing well. The combination of the bushing well and bushing insert perform the same function as a one piece integral loadbreak bushing, while providing the flexibility to change the bushing insert in the field, without taking the transformer or other apparatus out of service. The bushing insert and loadbreak elbows are the primary components in all ANSI/IEEE loadbreak connections.

The Chardon Bushing Insert incorporates an all copper current path. This provides reliable and consistent performance under all conditions.

The Chardon Bushing Insert meets all the requirements of IEEE Standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the bushing insert provides a fully shielded and fully submersible connection for loadbreak applications.

No special tools are required for installation. The bushing insert can be installed by hand or with the assistance of a torque tool. An internal hex broach allows for the installation by the torque tool.

# **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386.

- J Minimum Corona Voltage Level 11 kV
- / AC 1 Minute Withstand 34 kV

### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- Periodic Dissection
- Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	15 kV
Max. Rating Phase to Phase	14.4 kV
Max. Rating Phase to Ground	8.3 kV
AC 1 Minute Withstand	34 107
DC 15 Minute Withstand	53 kV
BIL and Full Wave Crest	95 kV
Minimum Corona Voltage Level	11 kV

#### + 15KV-8I-REV010615

# **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps res
Switching	10 operations at 200 amps rms at 14.4 kV
Fault Close	10,000 amps rms symmetrical at 14.4 kV for 0.17 s after 10 consecutive successful switching operations
ShortTime	10,000 amps rms symmetrical for 0.17 s     3,500 amps rms symmetrical for 3.0 s

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK BUSHING INSERT

## / LOCKING GROOVE

Lockling groove assures proper installation by 'lockling' into elbow.

## I ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

#### / STOP RING

Limits piston and finger contact travel during fault close.

#### / CONTACT

Copper component transfers current from piston contact to bushing well stud.

#### # CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

# / THREADED CONNECTION TO BUSHING WELL

3/8" - 16 UNC copper threads provided connection to bushing well.



#### I FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated in-house for complete control of rubber characteristics.

#### I DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector shield.

#### I HEX BROACH

5/16" hex broach permits installation with torque tool.

# ORDERING INFORMATION

15 kV, 200A Loadbreak Bushing Insert

15-LBI200





CÓDIGO

15-LE200

# TERMINAL DESCONECTÁVEL COTOVELO - TDC - 15kV-200A



The Chardon Loadbreak Elbow is a fully shielded, submersible and insulated termination for connecting underground cable to transformers, switchgear, and other apparatus equipped with loadbreak bushings, junctions, or other loadbreak connectors. The bushing insert and loadbreak elbows are the primary components in all ANSI/IEEE loadbreak connections.

The Chardon 15kV Loadbreak Elbow meets all the requirements of IEEE Standard 386, the interface design meets interface 78 (Fig 9 in IEEE Std 386-2016), and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. Chardon Loadbreak Elbows are molded using high quality

peroxide-cured insulating and semi-conducting EPDM rubber. All insulating rubber is compounded in house, using Chardon developed proprietary formulations.

Chardon Loadbreak Elbows include a stainless steel pulling eye. An optional capacitive test point is available. Included with the elbow kit is a bi-metal or copper compression connector, and a tin plated copper probe with arc quenching tip.

# **PRODUCTION TESTS**

#### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 11 kV
- I AC 1 Minute Withstand 34 kV
- / Test Point Voltage Test

#### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

# **VOLTAGE RATINGS**


Voltage Class	15 kV
Max. Rating Phase to Phase	14.4 107
Max. Rating Phase to Ground	8.3 KV
AC 1 Minute Withstand	34 WV
DC 15 Minute Withstand	53 kV
BIL and Full Wave Crest	95 EV
Minimum Corona Voltage Level	11 kV

Revision Date: 07.02.2024


# **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps ms
Switching	10 operations at 200 amps rms at 14.4 kV
Fault Close	10,000 amps rms symmetrikal at 14.4 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	• 10,000 amps rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s

# DETAILED COMPOSITION OF THE CHARDON 15 KV LOADBREAK ELBOW



# DETAILED COMPOSITION OF THE CHARDON 15 kV LOADBREAK ELBOW



# ORDERING INFORMATION

Chardon loadbreak Fuse Elbow kits are packaged in a heavy duty plastic bag.

## Each elbow kit includes the following:

/ Silicone Grease

/ Bi-Metal or Copper Compression Connector

/ Plated Copper Probe

/ Probe Installation Wrench

/ Installation Instructions

/ Elbow

## To order a Chardon 15 kV Fuse Elbow Kit, follow the steps below:

15-LE200	"M"	"X"	ıγı	"Z"
----------	-----	-----	-----	-----

"W"= Enter T if want a Capacitive Test Point

"X" = Cable Range Code (A, B, C or D)

"Y" = Conductor Code (See table)

"Z" = Enter C if a Plated Copper Connector is Desired (Bi-metal are standard)

#### Note

Bi-mataling for use on copper and aluminum conductors. Cooper lug for use on cooper conductors only.

### 15 kV, 200A Loadbreak Cable Ranges (Insulation Diameter)

Cable Range Code	Inches	Millimeters	
A	0.575 - 0.740	14.61 - 18.89	
В	0.640 - 0.905	16.26 - 22.99	
C	0.830 - 1.060	21.08 - 26.92	
D	0.936 - 1.220	23.62 - 30.99	

#### Conductor Code Table

ONDUCTOR	Concentric or C	ompressed	Compact	r Solid
CODE	AWG or kcmil	mm²	AWG or kcmil	mm²
01	#6		#4	
02	64	-	\$3	25
03	#3	25	#2	35
04	Ø2	35	<b>21</b>	-
05	#1	-	1/0	50
06	1/0	50	2/0	70
07	2/0	70	3/0	
08	3/0		4/0	95
09	4/0	95	250	120
10	250	120	300	-

#### Example:

To order a standard Chardon 15 kV Leadbreak Elbow with a cable insulation diameter of 0.850°, a 9/0 bi-metal compression connector, and a capacitive test point, order the following part number: 15-LE200TB08.







CÓDIGO 15-LFE200

# TERMINAL DESCONECTÁVEL COTOVELO - PORTA-FUSIVEIS 15kV-200A



The Chardon 15 kV Class Fused Loadbreak Elbow Connector combines a fully-shielded and insulated loadbreak elbow with full range current-limiting fuse protection. The Chardon Fused Loadbreak Elbow Connector provides a convenient and cost effective method to add fusing protection to underground distribution systems utilizing 200A, 15 kV Class loadbreak bushings. Designed as a hot stick operable switching device, it is tested at the maximum fuse rating in accordance with the IEEE 386 standard. The product is fully sealed and submersible.

Chardon Fused Loadbreak Elbow Connectors are molded using high quality peroxide-cured EPDM rubber, manufactured in Chardon's facilities, under strict quality controls. Standard features include a copper probe adapter, bimetal connector, plated copper loadbreak probe and a stainless steel reinforced pullingeye. The product is designed to accept a wide range of cable conductor and insulation sizes.

Chardon Fused Loadbreak Elbow Connectors are the ONLY fused elbow connectors on the market that can accept fuses manufactured by Cooper Power Systems (Eaton), Hi-Tech (ABB) and Chardon. This is accomplished by ordering the appropriate lug kit. This feature allows the customer an option which is not available on competitive products.

# **PRODUCTION TESTS**

#### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 11 kV
- # AC 1 Minute Withstand 34 kV
- I Test Point Voltage Test

### Tests conducted in accordance with Chardon manufacturing process requirements:

- I Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	15 kV
Max. Rating Phase to Phase	14.4 kV
Max. Rating Phase to Ground	8.3 kV
AC 1 Minute Withstand	34 kV
DC 15 Minute Withstand	53 kV
BLL and Full Wave Crest	95 kV
Minimum Corona Voltage Level	11 kV

 <sup>15</sup>LFE200-082318-REV05

# **CURRENT RATINGS**

Description	Test Parameters
Continuous	Fuse rating
Switching	10 operations at 200 amps rms at 14.4 kV
Fault Close	10,000 amps ms symmetrical at 14.4 kV for 0.47 s after 10 consecutive successful switching operations

# DETAILED COMPOSITION OF THE CHARDON 15KV LOADBREAK FUSE ELBOW



# DETAILED COMPOSITION OF THE CHARDON 15 KV LOADBREAK FUSE ELBOW




Fig 2: Dimension Info When CP5 Fuse or Chardon Fuse Installed.




Fig 3: Dimension Info When HI-Tech Fuse Installed.



Fig 4: Chardon Puse Elbow assemble with major fuses manufacturers.

# ORDERING INFORMATION

Chardon Loadbreak Fuse Elbow kits are packaged in a heavy duty plastic bag. Each elbow kit includes the following:

/ Fused Elbow, Cable Housing

Fused Elbow, Elbow Housing

/ Compression Lug Kit

/ Probe

/ Hex Wrench

/ Sillicone Lubricant

1 Towe

/ Instruction Sheet

Note:

Oursent-limiting fluses sold separately. See "Chardon Fuses" below for fluse recommendations, electrical satings and catalog numbers.

### To order a Chardon 15 kV Fuse Elbow Kit, follow the steps below:

15-LFE200T	"X"	"Y"	"Z"
------------	-----	-----	-----

"X" = Enter Cable Range Code (A, B, C or D)

"Y" = If a Hi-Tech Fuse will be used in the Fused Elbow, Enter"HE".

If a Cooper Fuse will be used in the Fused Elbow, enter "CE". If a Chardon Fuse will be used in the Fused Elbow, enter "CH".

"Z" = Enter Conductor Code (See Conductor Code Table Below)

Range Code	Inches	Millimeters
A	0.610 - 0.823	15.50 - 20.99
В	0.720 - 0.985	18.29 - 25.02
C	6.920 - 1.185	23.37 - 30.10
D	1.040 - 1.305	26.42 - 33.15

#### Conductor Code Table

CONDUCTOR	CTOR Concentric or Compressed		Compact	or Solid
CODE	AWG or kcmil	mm*	AWG or kcmil	rom <sup>a</sup>
01	#6		#4	
02	64	-	<b>#</b> 3	25
03	#3	25	12	35
04	#2	35	÷1	-
05	#1	ermenne ten	1/0	50
06	1/0	50	2/0	70
07	2/0	70	3/0	
08	3/0	•	4/0	95
09	4/0	95	250	120
18	250	120	300	-

: elq max

To order a Chardon 25 M Leadbreak Fused Elbow with a cable insulation diameter of 0.850°, using a HHzach fuse, and a 5/0 compression connector, order the following number: 15-LFE2007-B-HED8:

### Conductor Code Table

Compression Lug Kit	Part Number
Hi-Tech Fuse Compression Luig	LFEIGHTH + Conductor Code
Cooper Fuse Compression Lug	LFEK-CPS + Conductor Code
Chardon Fuse Compression Lug	LFEK-CH → Conductor Code

Elastimold, Hi-Tech, Easton and Cooper, these brand names are property of their respective owners. All company, product and service names used in this catalogy instruction sheet, are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.

# **CHARDON FUSES**



Table in Bectreical Characteristics of the Elbow Fuses and Catalog Numbers

_									
Voltage Class System(kV)	N o m i n a l Fuse Voltage Rating(kV)	e Voltage Fuse Current	Fuse Catalog Number	Minimum Melt I <sup>2</sup> t (A <sup>2</sup> s)	Maximum Total Pt (A <sup>2</sup> s)	Peak Arc Voltage (kV)	Maximum	Continuous	Current (A)
							25°C	40°C	65°C
		3	CHFEF083003	770	1700	33	4.9	4.7	4.2
		6	CHFEF083006	1390	3020	33	7.7	7.3	6.8
		8	CHFEF083008	1565	3600	33	8.3	7.9	8.5
	10	CHFEF083010	1760	3850	32	12.9	12.3	11.5	
	12	CHFEF083012	1850	4100	82	15.7	15.2	146	
	5 8.3	18	CHFEF083018	1950	7240	27	23.2	22.3	21.3
15		20	CHFEF083020	2120	7800	27	23.3	22.5	21.4
		25	CHFEF083025	2438	9600	27	28.5	27.5	26.7
		30	CHFEF083030	7330	15800	27	34.5	32.8	31
		40	CHFEF083040	7970	23700	27	45	42.5	40.5
		45	CHFEF083045	9752	31200	27	63	58	51
		65	CHFEF083065	19600	49700	16	89	84	80
		80	CHFEF083080	26250	66300	16	107	191	96

#### Table 2: Recommended Fuse Current Ratings for Transformer

Nominal Fuse Rated Voltage					8.3	kV					
			(19	Phase Volt	age Rating	(kV) - Pha	se to Grou	nd			
1-Phase Transformer kVA	2	4	4.	416		4,8		7.2		7.62	
	A	B	A	B	A	В	A	В	A	8	
10		8		6		6		6		6	
15	8	10		8		8		6		6	
25	12	20	10	12		10		8		8	
37.5	20	25	12	18	10	12		10		11	
50	25	40	18	20	12	20	10	12	10	1.	
75	40		20	30	20	30	12	20	12	2	
100			30		30	40	25	30	18	2	
167							40		30	4	

		3-Phase Voltage Rating (kV)-Phase to Phase										
3-Phase Transformer kVA	2.4		4.16		4.8		8.32		12,47		13.2 to 14.4kV	
	A	В	A	9	A	В	A	9	A	В	A	8
15		8										
22.5		10		6		6						
30	10	12		8		8		6				
45	12	20	10	10		10		6				
75	20	30	12	18	12	18		8		6		- 6
100	40		18	25	12	20		12		8		6
112.5			20	25	20	25	10	12		10		8
150			30	40	20	30	12	20		12		10
200			40		3.0	40	18	25		12	10	12
225					40		20	30	12	20	12	18
300							30	40	18	25	18	25
500									30	40	30	40

- (1) Fuses election is based on the continuous current rating of the fuses at 40°C. Fuses in listed Column A allow between 1.4 and 2 times the rated current of the transformer; those listed in Column 8, allow 2 to 3 times the rated current of the transformer.
  (2) Recommended fuses meetin rush criteria of 12 times transformer gull load current for 0.1 second and 25 times full load current for 0.01 second.
- (3) Fuses meeticald load pids up criteria of 6 times transformer full load current for 1 second and 3 times full load current of 16 seconds.





CÓDIGO 15-LFTI

# PLUGUE DE INSERÇÃO DUPLO PID - 15kV-200A



The Chardon Loadbreak Feed Thru Insert threads onto a standard 200A bushing well and provides dual loadbreak bushing interfaces. It can convert radial-feed transformers to feedthru transformers and add in-line arrester protection if needed. The torque limit ratchet feature prevents the bushing well stud from breaking during installation. The ratchet feature allows users to rotate the feed thru insert for 360° to orient the feedthru insert in the desired position.

The Chardon Loadbreak Feed Thru Insert meets all the requirements of IEEE Standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the bushing insert provides a fully shielded and fully submersible connection for loadbreak applications.

# **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 11 kV
- / AC 1 Minute Withstand 34 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

# **VOLTAGE RATINGS**


Voltage Class	15 KV
Max. Rating Phase to Phase	14.4 kk
Max. Rating Phase to Ground	8.3 KV
AC 1 Minute Withstand	34 KV
DC 15 Minute Withstand	53 KV
BL and Full Wave Crest	95 kV
Minimum Corona Voltage Level	11 kV

15-LFTI200-080623-REV03

# **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps rms
Switching	10 operations at 200 amps rms at 14.4 kV
Famil: Close	10,000 amps rms symmetrical at 14.4 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	10,000 amps rms symmetrical for 0.17 s     3,500 amps rms symmetrical for 3.0 s

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK FEED THRU INSERT



# ORDERING INFORMATION

15kV,200A Loadbreak Feed Thru Insert

15-LFTI


#### Each kit contains:

- / Rotatable Feed Thru Insert
- Shipping Cap (not for energized operation)
- Stainless Steel Bail Assembly
- / Silicone Lubricant
- / Installation Instruction Sheet

#### Replacement Part

**Bail Assembly** 

15-BAIL-LFTI







CÓDIGO 15-LIB130 / 15-LIB185

# BUCHA DE LIGAÇÃO DE EQUIPAMENTO - BLE - 15kV-200A



The Chardon Integral Bushing is designed for installing to transformer, switchgear and other equipment and is used as a mating loadbreak connector for elbow, elbow arrester or grounding elbow. An integral skirt feature can

be applied to oil or SF6 insulating equipment. It has arc extinction function to ensure the loadbreak application. The indicated ring on the interface can be easily known from outside if the installation is in place or not.

# **KEY FEATURES**

- Provides a fully shielded and submersible connection when mate with the standard bushing.
- / Meet ANSI/IEEE Std. 386 interface.
- / No minimum phase clearance requirements.

# **VOLTAGE RATINGS AND CHARACTERISTICS**

Description	
Standard Voltage Class	15kV
AC Withstand	39kV/5min
BiL and Full Wave Crest(Impaise)	95kV
Minimum Corona Voltage Level	15Kvs10pC

# **CURRENT RATINGS AND CHARACTERISTICS**


Description	Amperes
Continuous	200 A mss
Thermal Short Circuit	8.7kA/1s
Dynamic Short Circuit	21 <sub>n</sub> 2kA/10ms

# **PRODUCTION TESTS**

## Tests conducted in accordance with ANSI/IEEE Stnd.386, GB/T 12706.4

- / Minimum Corona Voltage Level 15kV <3pC (100%Test)
- J AC Withstand 42kV /1min (100%Test)
- / BilL and Full Wave Crest (Impulse)- 95 kV (Sampling Test)

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK INTEGRAL BUSHING



# ORDERING INFORMATION

15-LIB130 (Standard) / 15-LIB185 (Extended Length)

Standard M10 Thread Mild Steel-Zinc Dichromate plating Clamp	15-LIB130M103ZD
Standard M 10 Thread Stainless Steel Clamp	15-LIB130W1035S
Standard M12 Thread Mild Steel-Zinc Dichromate plating Clamp	15-LIB130M123ZD
Standard M12Thread Stainless Steel Clamp	15-LIB130M123SS
Extended Length M10 Thread Mild Steel-Zinc Dichromate plating Clamp	15-LIB185M103ZD
Extended Length M10 Thread Stainless Steel Clamp	15-LIB185M103SS
Extended Length M12 Thread Mild Steel-Zinc Dichromate plating Clamp	15-UB185M123ZD
Extended Length M12 Thread Stainless Steel Clamp	15-LIB185M12355





CÓDIGO 15-LIC200

# RECEPTÁCULO ISOLANTE BLINDADO - RIB - 15kV-200A



The Chardon Protective Cap is an accessory product to other 15 kV, 200A products with loadbreak interfaces (bushing inserts, loadbreak junctions, feed thru inserts, etc.). It is designed to physically seal and electrically insulate loadbreak bushing interfaces. When installed on a loadbreak bushing interface, and

properly grounded using the attached drain wire, the Loadbreak Protective Cap provides a submersible, fully shielded insulated cap for energized bushings.

The Loadbreak Protective Cap can be used for temporary or permanent applications.

# **PRODUCTION TESTS**

#### Tests conducted in accordance with IEEE/ANSI Standard 386.

Minimum Corona Voltage Level – 11 kV

/ AC 1 Minute Withstand - 34 kV

#### Tests conducted in accordance with Chardon manufacturing process requirements:

/ Physical Inspection

/ Periodic Dissection

/ Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	.15 kV
Max. Rating Phase to Phase	14.4 NV
Max. Rating Phase to Ground	83 kV
AC 1 Minute Withstand	34 kV
DC 15 Minute Withstand	53 kV
BiL and Full Wave Crest	95 kV
Minimum Corona Voltage Level	11 kV

-Revision Date: 12.21.2023

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK PROTECTIVE CAP

#### I DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector shield. A drain wire is included with the product.

#### I SEMICONDUCTING INSERT

Precision molded peroxide cured semiconducting insert provides corona-free electrostatic shielding of the connector.

#### / LATCHING RING

Semiconducting molded locking ring secures cap on nose piece of mating product.

#### I INSULATION LAYER

High quality peroxide cured EPDM Insulation is mixed and formulated in-house for complete control of rubber characteristics.

# / PULLING EYE


Molded in stainless steel pulling eye insures high strength for hotstick operation.

#### / SEMICONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

#### / PROBE

Brass probe provides reliable conductive path with mating female contacts.



# @2.78" (70.5mm)

# ORDERING INFORMATION

15 kV, 200A Loadbreak Protective Cap

15-LIC200





CÓDIGO 1

15-LJ200

# BARRAMENTO DE DERIVAÇÃO 15kV-200A



The Chardon 200 A, 15 kV Class Loadbreak Junction provides two, three or four 8.3/14.4 kV loadbreak interfaces that are internally bused together and meet all requirements of IEEE Standard 386™ --- Separable Insulated Connector Systems, Loadbreak junctions are used in pad-mounted apparatus, underground vaults, and other apparatus to sectionalize, establish loops, taps, or splices, and to facilitate apparatus changeouts.

Sectionalizing a cable run to find and isolate a cable fault is made easy when a loadbreak iunction is used with 15 kV Class Loadbreak elbows and other accessories meeting the requirements of IEEE Standard 386™.

The Chardon Loadbreak design incorporates an all copper current carrying path, which provides reliable and consistent performance under all conditions.

The Chardon Loadbreak Junction meets all the requirements of IEEE standard 386, and is fullying interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the loadbreak junction provides a fully shielded connection for loadbreak applications.

# PRODUCTION TESTS

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 11 kV
- J AC 1 Minute Withstand 34 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- I Physical Inspection
- 1 Periodic Dissection
- Periodic X-ray Analysis

# **VOLTAGE RATINGS**


Voltage Class	15 kV
Max. Rating Phase to Phase	14.4 kV
Max. Rating Phase to Ground	8.3 kV
AC 1 Minute Withstand	34 kV
DC 15 Minute Withstand	53 kV
BIL and Fall Wave Crest	95 kV
Minimum Corona Voltage Level	11 kV

<sup>+15</sup>LJ200-072718-REV03

# **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps res
Switching	10 operations at 200 amps rms at 14.4 kV
Fault Close	10,000 amps rms symmetrical at 14.4 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	10,000 amps rms symmetrical for 0.17 s     3,500 amps rms symmetrical for 3.0 s

# **DETAIL COMPOSITION OF THE** CHARDON LOADBREAK JUNCTION



#### / LOCKING GROOVE

Locking groove assures propera installation by "locking" into elbow.

#### I FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated inhouse for complete control of rubber

#### / CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

# ORDERING INFORMATION

15kV, 200A Loadbreak Junction

#### Each kit contains:

- / Loadbreak Junction (with mounted bracket or straps, depending on product ordered)
- / Shipping Caps (not for energized operation)
- / Silicone Lubricant
- / Installation Instruction Sheet


## To order a Chardon 15 kV Fuse Elbow Kit, follow the steps below:

Part Description	Junction Only	Junction with bracket	Junction with U-Straps
15kV 200A Jauction-2	15-LJ200F2	15-LJ200F2SS	15-LJ200F2U
15kV 200A Junction-3	15-LJ200F3	15-LJ200F3SS	15-LJ200F3U
15kV 200A Jaaction-4	15-LJ200F4	15-LJ200F-859	15-LJ200F4U

## Replacement Parts:

Catalog Number
15/25-LJ200U
15-LJBKTF2
15-LJBKTF3
15-LJBKTF4


## Junction with Bracket Dimensional Information




	15kV
Stacki	ng Dimensions
57	0.8*(21mm)
59	3.2° §8 (mm)
510	6.1"(156mm)
511	7.5"(191nm)
M4	See Dimensional Information

	Physical Dimensions In. (mm)		Physical Dimensions M4 Mounting Dimensions in.(mm)					
Number of Interfaces			Configuraation1 C		Configu	Configuration2		Configuraation3
	A	В	Min.	Max.	Min.	Max	Min.	Max
2	15.4 (390)	6.5 (164)	11.8 (300)	15.7 (400)	8.4 (213)	12.3 (313)	5.0 (126)	8.9 (226)
3	18.5 (470)	9.4 (239)	15.0 (380)	18.9 (480)	11.5 (293)	15.5 (393)	8.1 (206)	12.0 (306)
4	21.7 (550)	12.6 (321)	18.1 (460)	22.0 (560)	14.7 (373)	18.6 (473)	11.3 (28 6)	15.2 (386)

\* Configuration 1, Both feet turned out. Configuration 3. One foot turned out, one in. Configuration 3. Both feet turned in.



# Junction with U-straps Dimensional Information







CÓDIGO 15-LPFT200

# PLUGUE DE BY-PASS - PBP 15kV-200A



**GRUPO** 





25-LE200

# TERMINAL DESCONECTÁVEL COTOVELO - TDC - 25kV-200A



The Chardon Loadbreak Elbow is a fully shielded, submersible and insulated termination for connecting underground cable to transformers, switchgear, and other apparatus equipped with loadbreak bushings, junctions, or other loadbreak connectors. The bushing insert and loadbreak elbows are the primary components in all ANSI/IEEE loadbreak connections.

The Chardon 35kV Loadbreak Elbow meets all the requirements of IEEE Standard 386, the interface design meets interface 7B (Fig 9 in IEEE Std 386-2016), and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. Chardon Loadbreak Elbows are molded using high quality

peroxide-cured insulating and semi-conducting EPDM rubber. All insulating rubber is compounded in house, using Chardon developed proprietary formulations.

Chardon Loadbreak Elbows include a stainless steel pulling eye. An optional capacitive test point is available. Included with the elbow kit is a bi-metal or copper compression connector, and a tin plated copper probe with arc quenching tip.

# **PRODUCTION TESTS**

#### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 19 kV
- / AC 1 Minute Withstand 40 kV
- Test Point Voltage Test

#### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

#### • Revision Date: 12.19.2024


# **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps rms
Switching	10 operations at 200 amps rms at 26.3 kV
Fault Close	10,000 amps rms symmetrical at 26.3 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	• 10,000 amps rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s

# DETAILED COMPOSITION OF THE CHARDON 25 KV LOADBREAK ELBOW



# DETAILED COMPOSITION OF THE CHARDON 25 KV LOADBREAK ELBOW



# **ORDERING INFORMATION**

Chardon Loadbreak Fuse Elbow kits are packaged in a heavy duty plastic bag.

Each elbow kit includes the following:

/ Silicone Grease

/ Bi-Metal or Copper Compression Connector

/ Plated Copper Probe

/ Installation Instructions

Probe Installation WrenchElbow

To order a Chardon 25 kV Elbow Kit, follow the steps below:

25-LE200 "W" "X" "Y" "2	11
-------------------------	----

"W" = Enter T if want a Capacitive Test Point

"X" = Cable Range Code (A, B, C or D)

"Y" = Conductor Code (See table)

"Z" = Enter C if a Plated Copper Connector is needed Enter B if a Bi-metal Connector is needed

## 25 kV, 200A Loadbreak Cable Ranges (Insulation Diameter)

Cable Range Code	Inches	Millimeters
Α	0.610 - 0.875	15.49 - 22.23
В	0.720 - 0.985	18.29 - 25.02
C	0.920 - 1.185	23.37 - 30.10
D	1.040 - 1.305	26.42 - 33.15

#### **Conductor Code Table**

CONDUCTOR	Concentric o	r Compressed	Compact or Solid		
CODE	AWG or kcmil	mm²	AWG or kcmil	mm²	
01	#6	-	#4	-	
02	#4	-	#3	25	
03	#3	25	#2	35	
04	#2	35	#1	-	
05	#1	-	1/0	50	
06	1/0	50	2/0	70	
07	2/0	70	3/0	-	
08	3/0	-	4/0	95	
09	4/0	95	250	120	
10	250	120	300	-	

Example

To order a standard Chardon 25 kV Loadbreak Elbow with a cable insulation diameter of 0.990", a 3/0 bi-metal compression connectorand a capacitive test point, order the following part number: 25-LE200TC08B.

www.chardongroup.com

The Chardon 200A, 15kV Class Loadbreak Portable Feed Thru is designed to be installed on a parking stand, attached to a transformer or other apparatus. Two bushing insert loadbreak interfaces can be mated with an elbow arrester, a loadbreak elbow, or an insulated cap. When mated with other products that meets IEEE Standard 386, the Portable Feed Thru provides a fully shielded, submersible connection for loadbreak operation.

The Chardon Portable Feed Thru meets all the requirements of IEEE Standard 386, and is fully interheangeable with competetior's products and mating products that also meet IEEE Standard 386. The indicating ring design eliminates the guesswork of loadbreak installation, it provides feedback to determine if the elbow is properly installed.

# **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386.

Minimum Corona Voltage Level – 11 kV

/ AC 1 Minute Withstand - 34 kV

## Tests conducted in accordance with Chardon manufacturing process requirements:

J Physical Inspection

1 Periodic Dissection

/ Periodic X-ray Analysis

# **VOLTAGE RATINGS**


Voltage Class	15 kV
Max. Rating Phase to Phase	14.4 k%
Max. Rating Phase to Ground	8.3 kV
AC 1 Minute Withstand	34 107
DC 15 Minute Withstand	53 kV
BIL and Fall Wave Crest	95 KV
Minimum Corona Voltage Level	11 kV

 <sup>15</sup>LPFT2094022719-REV01

# **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 ampsines
Switching	10 operations at 200 amps rms at 14.4 kV
Fault Close	10,000 amps rms symmetrical at 14.4 MV for 0.17 s after 10 consecutive successful switching operations
Short Time	10,000 amps rms symmetrical for 0.17 s     3,500 amps rms symmetrical for 3.0 s

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK PORTABLE FEED THRU



#### / LOCKING GROOVE

Locking groove assures propera installation by "locking" into elbow.

#### / FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated inhouse for complete control of rubber resistance.

#### / CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.


# ORDERING INFORMATION

## Each Portable Feed Thru kit includes the following:

- / Portable Feed Thru with Bracket
- / Shipping Caps (not for energized operation)
- / Installation Instruction Sheet

15kV Loadbreak Portable Feed Thru

15-LPFT200







25-LBI200

# PLUGUE DE INSERÇÃO SIMPLES PIS - 25kV-200A



The Chardon Bushing Insert threads onto a standard 200A bushing well. The combination of the bushing well and bushing insert perform the same function as a one piece integral loadbreak bushing, while providing the flexibility to change the bushing insert in the field, without taking the transformer or other apparatus out of service. The bushing insert and loadbreak elbows are the primary components in all ANSI/IEEE loadbreak connections.

The Chardon Bushing Insert incorporates an all copper current path. This provides reliable and consistent performance under all conditions.

The Chardon Bushing Insert meets all the requirements of IEEE Standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the bushing insert provides a fully shielded and fully submersible connection for loadbreak applications.

No special tools are required for installation. The bushing insert can be installed by hand or with the assistance of a torque tool. An internal hex broach allows for the installation by the torque tool.

# **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 19 kV
- / AC 1 Minute Withstand 40 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- Physical Inspection
- / Periodic Dissection
- Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

## • 25-LBI200-122518-REV01

# **CURRENT RATINGS**

Description	Test Parameters			
Continuous	200A rms			
Switching	10 operations at 200A rms at 26.3 kV			
Fault Close	10,000A rms symmetrical at 26.3 kV for 0.17 s after 10 consecutive successful switching operations			
Short Time	• 10,000A rms symmetrical for 0.17s • 3,500 amps rms symmetrical for 3.0s			

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK BUSHING INSERT

#### **/LOCKING GROOVE**

Locking groove assures proper installation by "locking" into elbow.

#### / ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

#### / STOP RING

Limits piston and finger contact travel during fault close.

#### / DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector shield.

#### / SEMICONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.



#### / FINGER CONTACT

Silver plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / INSULATION LAYER

High quality peroxide cured EPDM Insulation is mixed and formulated in-house for complete control of rubber characteristics.

#### / HEX BROACH

5/16" hex broach permits installation with torque tool.

# / THREADED CONNECTION TO BUSHING WELL

3/8"-16 UNC copper threads provided connection to bushing well.

# **ORDERING INFORMATION**

25 kV, 200A Loadbreak Bushing Insert

25-LBI200





25-LJ200

# BARRAMENTO DE DERIVAÇÃO 25kV-200A



The Chardon 200 A, 25 kV Class Loadbreak Junction provides two, three or four 15.2/26.3 kV loadbreak interfaces that are internally bused together and meet all requirements of IEEE Standard 386™ — Separable Insulated Connector Systems. Loadbreak Junctions are used in padmounted apparatus, under-ground vaults, and other apparatus to sectionalize, establish loops, taps, or splices, and to facilitate apparatus changeouts.

Sectionalizing a cable run to find and isolate a cable fault is made easy when a loadbreak iunction is used with 25 kV Class Loadbreak elbows and other accessories meeting the requirements of IEEE Standard 386™. The Chardon Loadbreak design incorporates an all copper current carrying path, which provides reliable and consistent performance under all conditions.

The Chardon Loadbreak Junction meets all the requirements of IEEE standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the loadbreak junction provides a fully shielded connection for loadbreak applications.

# **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

/ Minimum Corona Voltage Level – 19 kV

AC 1 Minute Withstand – 40 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

<sup>· 25</sup>LJ200- 042220-REV04

# **CURRENT RATINGS**

Description	Test Parameters			
Continuous	200 amps rms			
Switching	10 operations at 200 amps rms at 26.3 kV			
Fault Close 10,000 amps rms symmetrical at 2 for 0.17 s after 10 consecutive successitching operations				
Short Time	• 10,000 amps rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s			

# DETAIL COMPOSITION OF THE CHARDON LOADBREAK JUNCTION

## / ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operation.

#### / STOP RING


Limit piston and finger contact travel during fault close.

#### / CONTACT

Copper component transfers current from piston contact to bushing well stud.

#### / COPPER BUS BAR

Provide consistent current carry capability during operation.



#### / LOCKING GROOVE

Locking groove assures a proper installation by "locking" into elbow.

#### / FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated inhouse for complete control of rubber resistance.

#### **I** CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

# **ORDERING INFORMATION**

#### Each kit contains:

- I Loadbreak Junction (with mounted bracket or straps, depending on product ordered)
- Shipping Caps (not for energized operation)
- / Silicone Grease
- Installation Instruction Sheet

# ORDERING INFORMATION


## **Loadbreak Junction Part Numbers**

Part Description	Junction Only	Junction with bracket	Junction with U-Straps	
25kV 200A Junction-2	25-LJ200F2	25-LJ200F2SS	25-LJ200F2U	
25kV 200A Junction-3	25-LJ200F3	25-LJ200F3SS	25-LJ200F3U	
25kV 200A Junction-4	25-LJ200F4	25-LJ200F4SS	25-LJ200F4U	

## **Replacement Parts**

Description	Catalog Number	
U-Strap Kit (1 Strap)	15/25-LJ200U	
Stainless Steel Bracket -2 way	25-LJBKTF2	
Stainless Steel Bracket -3 way	25-LJBKTF3	
Stainless Steel Bracket -4 way	25-LJBKTF4	


### **Junction with Bracket Dimensional Information**




25kV			
Stacking Dimensions			
<b>S7</b>	0.8" (21mm)		
S9	3.2" (81mm)		
S10	7.5" (191mm)		
S11	8.9" (226mm)		
M4	See Dimensional		


	Physical Dimensions In. (mm)		M4 Mounting Dimensions in.(mm)					
Number of Interfaces			In. (mm) Configuraation1		Configuraation2		Configuraation3	
	А	В	Min.	Max.	Min.	Max.	Min.	Max.
2	16.1 (410)	7.2 (184)	12.6 (320)	16.5 (420)	9.2 (233)	13.1 (333)	5.7 (146)	9.7 (246)
3	20.1 (510)	10.9 (277)	16.5 (420)	20.5 (520)	13.1 (333)	17.0 (433)	9.7 (246)	13.6 (346)
4	24.0 (610)	14.9 (379)	20.5 (520)	24.4 (620)	17.0 (433)	21.0 (533)	13.6 (346)	17.6 (446)

<sup>\*</sup> Configuration 1. Both feet turned out. Configuration 2. One foot turned out, one in. Configuration 3. Both feet turned in.



# **Junction with U-straps Dimensional Information**









25-LFTI

# PLUGUE DE INSERÇÃO DUPLO PID - 25kV-200A



The Chardon Loadbreak Feed Thru Insert threads onto a standard 200A bushing well and provides dual loadbreak bushing interfaces. It can convert radial-feed transformers to feed thru transformers and add in-line arrester protection if needed. The torque limit ratchet feature prevents the bushing well stud from breaking during installation. The ratchet feature allows users to rotate the feed thru insert for 360° to orient the feed thru insert in the desired position.

The Chardon Loadbreak Feed Thru Insert meets all the requirements of IEEE Standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the bushing insert provides a fully shielded and fully submersible connection for loadbreak applications.

# **PRODUCTION TESTS**

#### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 19 kV
- / AC 1 Minute Withstand 40 kV

## Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- Periodic Dissection
- Periodic X-ray Analysis

# **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

<sup>· 25-</sup>LFTI200-030623-REV04

# **CURRENT RATINGS**

Description	Test Parameters			
Continuous	200 amps rms			
Switching	10 operations at 200 amps rms at 26.3 kV			
Fault Close	10,000 amps rms symmetrical at 26.3 kV f 0.17 s after 10 consecutive successful switchin operations			
Short Time	• 10,000 amps rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s			

# DETAILED COMPOSITION OF THE CHARDON LOADBREAK FEED THRU INSERT

#### **I** ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

#### / STOP RING

Limits piston and finger contact travel during fault close.

#### / FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated in-house for complete control of rubber resistance.

#### / COPPER BUS BAR

Provide consistent current carry capability during operation.

## **/**LOCKING GROOVE

Locking groove assures proper installation by "locking" into elbow.

#### / INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

#### **/** CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

#### **I** TORQUE-LIMITING RATCHET

The ratchet feature allows users to rotate the feedthru insert for 360° to orient the feedthru insert in the desired position and protect the stud from damaging.

/ 3/8- 16 UNC Threads

# **ORDERING INFORMATION**

#### 25kV,200A Loadbreak Feed Thru Insert

25-LFTI


#### Each kit contains:

- / Rotatable Feed Thru Insert
- Shipping Cap (not for energized operation)
- Stainless Steel Bail Assembly
- / Silicone Lubricant
- Installation Instruction Sheet

### **Replacement Part**

**Bail Assembly** 

25-BAIL-LFTI







25-LPFT200

# PLUGUE DE BY-PASS PBP 25kV-200A



The Chardon 200A, 25kV Class Loadbreak Portable Feed Thru is designed to be installed on a parking stand, attached to a transformer or other apparatus. Two bushing insert loadbreak interfaces can be mated with an elbow arrester, a loadbreak elbow, or an insulated cap. When mated with other products that meets IEEE Standard 386, the portable feed thru provides a fully shielded, submersible connection for loadbreak operation.

The Chardon Portable Feed Thru meets all the requirements of IEEE Standard 386, and is fully interhoangeable with competetior's products and mating products that also meet IEEE Standard 386. The indicating ring design eliminates the guesswork of loadbreak installation, it provides feedback to determine if the elbow is properly installed.

### **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 19 kV
- / AC 1 Minute Withstand 40 kV

### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **VOLTAGE RATINGS**


Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

<sup>· 25</sup>LPFT200-051116-REV01

### **CURRENT RATINGS**

<b>5</b>	
Description	Test Parameters
Continuous	200 amps rms
Switching	10 operations at 200 amps rms at 26.3 kV
Fault Close	10,000 amps rms symmetrical at 26.3 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	• 10,000 amps rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s

### DETAILED COMPOSITION OF THE CHARDON LOADBREAK PORTABLE FEED THRU



### / LOCKING GROOVE

Locking groove assures propera installation by "locking" into elbow.

### / FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

### / INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

#### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated inhouse for complete control of rubber resistance

### **/** CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

### **ORDERING INFORMATION**

### Each Portable Feed Thru kit includes the following:

- Portable Feed Thru with Bracket
- Shipping Cap (not for energized operation)
- / Stainless Steel Bail Assembly
- Installation Instruction Sheet

To order the 25kV Class Portable Feed Thru Kit,use the P/N below:

25kV Loadbreak Portable Feed Thru


bushing well stud.


**I COPPER BUS BAR** 

Provide consistent current carry

capability during operation.

25-I PFT200









25-ETP600 25-LRTP600

## PLUGUE DE REDUÇÃO PR 25kV-600/200A



The Chardon Elbow Tap Plug (ETP) and Load Reducing Tap Plug (LRTP) are used to convert a standard 600A deadbreak interface to a standard 200A loadbreak interface.

The ETP is ideal for applications where a 200A tap is desired for test or ground purposes. The ETP is also ideal for adding a 200A tap to an existing 600A T-Body connector. The 200A interface allows for live test, visible ground, addition of a 200A tap, or installation of an elbow arrester.

The LRTP is ideal for applications where the termination will be separated to achieve a visible break and ground. Having the T-body and LRTP connected, as one unit, makes it easier to install and remove from the mating bushing interface. The 200A interface allows for live test, phasing, and visible ground. In

addition, it can be used to add a 200A tap, or for the installation of an elbow arrester. The LRTP has a factory installed alignment guide with a shear pin that allows the alignment guide to disengage after installation. When the LRTP is screwed into the threaded insert of a bushing extender or threaded 600/900A compression connector, the alignment guide disengages once the proper amount of torque is applied.

Both the ETP and LRTP meet all the requirements of IEEE Standard 386, and are 200A three phase switching and three phase fault close rated.

The Chardon ETP and LRTP incorporate an all copper current path. This provides reliable and consistent performance under all conditions.

### **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

Minimum Corona Voltage Level – 19 kVAC 1 Minute Withstand – 40 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

Physical Inspection

/ Periodic Dissection

/ Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

### **CURRENT RATINGS**

	Description	Amperes
600A Interface	Continuous	600A rms
	Short Time	• 25,000A rms symmetrical for 0.17 s • 10,000A rms symmetrical for 3.0 s
200A Interface	Continuous	200A rms
	Switching	10 operations at 200 amps rms at 26.3 kV
	Fault Close	10,000A rms symmetrical at 26.3 kV for 0.17 s after 10 consecutive successful switching operations
	Short Time	• 10,000A rms symmetrical for 0.17s • 3,500A rms symmetrical for 3.0 s

Note

System design and protection must recognize the ratings of 200A interface.

### DETAILED COMPOSITION OF THE CHARDON ELBOW TAP PLUG (ETP)

### DETAILED COMPOSITION OF THE CHARDON LOAD REDUCING TAP PLUG (LRTP)

### / LOCKING GROOVE

Locking groove assures proper installation by "locking" into elbow.

#### **I** ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

### I FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

### **ISEMICONDUCTING SHIELD**

Precision molded peroxide cured semiconducting shield provides ground shield continuity and meets the requirements of IEEE Standard 592.

#### / HEX BROACH

5/16" hex broach permits installation with torque tool.

600A INTERFACE



### / STOP RING

Limits piston and finger contact travel during fault close.

#### / DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector shield

### / INSULATION LAYER

High quality peroxide cured EPDM Insulation is mixed and formulated in-house for complete control of rubber characteristics.

#### / THREADED CONNECTION TO T-BODY

5/8" – 11 UNC copper threads provided connection to T-Body connector.

### **/** LOCKING GROOVE

Locking groove assures proper installation by "locking" into elbow.

### **/** ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

### / FINGER CONTACT

Tim plated copper contact provides a consistent current transfer during switching and fault close operations.

### **I** SEMICONDUCTING SHIELD

Precision molded peroxide cured semiconducting shield provides ground shield continuity and meets the requirements of IEEE Standard 592.

### / THREADED CONNECTION TO T-BODY

5/8" – 11 UNC threads provided connection to T-Body connector.

### 200A INTERFACE



### **ISTOP RING**

Limits piston and finger contact travel during fault close.

#### / INSULATION LAYER

High quality peroxide cured EPDM Insulation is mixed and formulated inhouse for complete control of rubber characteristics.

### **I HEX BROACH**

5/16" hex broach permits installation with torque tool.

### **✓ THREADED CONNECTION TO T-BODY**

15/16" – 9 NS 2A stationary threads mate with 600A compression connector or bushing extender.

### 600A INTERFACE

### **ORDERING INFORMATION**

25 kV, 600A Load Reducing Tap Plug

25-LRTP600

### **ORDERING INFORMATION**

25 kV, 600A Elbow Tap Plug

25-ETP600





25-LIC200

## RECEPTÁCULO ISOLANTE BLINDADO - RIB - 25kV-200A



The Chardon Protective Cap is an accessory product to other 25 kV, 200A products with loadbreak interfaces (bushing inserts, loadbreak junctions, feed thru inserts, etc.). It is designed to physically seal and electrically insulate loadbreak bushing interfaces. When installed on a loadbreak bushing interface, and

properly grounded using the attached drain wire, the Loadbreak Protective Cap provides a submersible, fully shielded insulated cap for energized bushings.

The Loadbreak Protective Cap can be used for temporary or permanent applications.

### **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386.

/ Minimum Corona Voltage Level – 19 kV

/ AC 1 Minute Withstand - 40 kV

### Tests conducted in accordance with Chardon manufacturing process requirements:

/ Physical Inspection

/ Periodic Dissection

Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

• 25LIC200-062123-REV02

### DETAILED COMPOSITION OF THE CHARDON LOADBREAK PROTECTIVE CAP

### / DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector shield.

### / SEMICONDUCTING INSERT

Precision molded peroxide cured semiconducting insert provides corona-free electrostatic shielding of the connector.

### /LATCHING RING

Semiconducting molded locking ring secures cap on nose piece of mating product.

### / INSULATION LAYER

High quality peroxide cured EPDM Insulation is mixed and formulated in-house for complete control of rubber characteristics.

### / PULLING EYE


Molded in stainless steel pulling eye insures high strength for hotstick operation.

#### / SEMICONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

#### / PROBE

Brass probe provides reliable conductive path with mating female contacts.



### **ORDERING INFORMATION**

25 kV, 200A Loadbreak Protective Cap

25-LIC200





25-LFE200

## TERMINAL DESCONECTÁVEL COTOVELO - PORTA-FUSIVEIS 25kV-200A



The Chardon 25 kV Class Fused Loadbreak Elbow Connector combines a fully-shielded and insulated loadbreak elbow with full range current-limiting fuse protection. The Chardon Fused Loadbreak Elbow Connector provides a convenient and cost effective method to add fusing protection to underground distribution systems utilizing 200 A, 25 kV Class loadbreak bushings. Designed as a hot stick operable switching device, it is tested at the maximum fuse rating in accordance with the IEEE 386-2006 standard. The product is fully sealed and submersible.

Chardon Fused Loadbreak Elbow Connectors are molded using high quality peroxide-cured

EPDM rubber, manufactured in Chardon's facilities, under strict quality controls. Standard features include a copper probe adapter, bimetal connector, plated copper loadbreak probe and a stainless steel reinforced pullingeye. The product is designed to accept a wide range of cable conductor and insulation sizes.

Chardon Fused Loadbreak Elbow Connectors are the ONLY fused elbow connectors on the market that can accept fuses manufactured by Cooper Power Systems (Eaton) and Hi-Tech (ABB). This is accomplished by ordering the appropriate lug kit. This feature allows the customer an option which is not available on competitive products.

### **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 19 kV
- / AC 1 Minute Withstand 40 kV
- I Test Point Voltage Test

### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	25 kV
Max. Rating Phase to Phase	26.3 kV
Max. Rating Phase to Ground	15.2 kV
AC 1 Minute Withstand	40 kV
DC 15 Minute Withstand	78 kV
BIL and Full Wave Crest	125 kV
Minimum Corona Voltage Level	19 kV

<sup>· 25</sup>LFE200-082718-REV03

### **CURRENT RATINGS**

Description	Test Parameters
Continuous	Fuse rating
Switching	10 operations at 200 amps rms at 26.3 kV
Fault Close	10,000 amps rms symmetrical at 26.3 kV for 0.17 s after 10 consecutive successful switching operations

### DETAILED COMPOSITION OF THE CHARDON 25KV LOADBREAK FUSE ELBOW




Fig 1: Detail Chardon Fuse Elbow Composition (CPS fuse installed)

### DETAILED COMPOSITION OF THE CHARDON 25KV LOADBREAK FUSE ELBOW




Fig 2: Dimension Info When CPS Fuse or Chardon Fuse Installed.




Fig 3: Dimension Info When Hi-Tech Fuse Installed.

### **ORDERING INFORMATION**

Chardon Loadbreak Fuse Elbow kits are packaged in a heavy duty plastic bag. **Each elbow kit includes the following:** 

Fused Elbow, Cable Housing

/ Fused Elbow, Elbow Housing

/ Compression Lug Kit

/ Probe

/ Hex Wrench

Silicone Grease

Towel

/ Installation Instruction Sheet

Note:

Current-limiting fuses sold separately. See "Chardon Fuses" below for fuse recommendations, electrical ratings and catalog numbers.

### To order a Chardon 25 kV Fuse Elbow Kit, follow the steps below:

25-LFE200T "X" "Y" "Z"	
------------------------	--

"X" = Enter Cable Range Code (A, B, C or D)

"Y" = If a Hi-Tech Fuse will be used in the Fused Elbow, Enter "HE".

If a Cooper Fuse will be used in the Fused Elbow, enter "CP".

If a Chardon Fuse will be used in the Fused Elbow, enter "CH".

"Z" = Enter Conductor Code (See Conductor Code Table Below)

Range Code	Inches	Millimeters
Α	0.610 - 0.823	15.50 - 20.90
В	0.720 - 0.985	18.29 - 25.02
C	0.920 - 1.185	23.37 - 30.10
D	1.040 - 1.305	26.42 - 33.15

### **Conductor Code Table**

CONDUCTOR	Concentric o	r Compressed	Compact or Solid		
CODE	AWG or kcmil	mm²	AWG or kcmil	mm²	
01	#6	-	#4	-	
02	#4	-	#3	25	
03	#3	25	#2	35	
04	#2	35	#1	-	
05	#1	-	1/0	50	
06	1/0	50	2/0	70	
07	2/0	70	3/0	-	
08	3/0 -	4/0	95		
09	4/0	95	250	120	
10	250	120	300	-	

Example :

To order a Chardon 25 kV Loadbreak Fused Elbow with a cable insulation diameter of 0.850", using a Hi-tech fuse, and a 3/0 compression connector, order the following number: 15-LFE200T-B-HE08.

### **ORDERING INFORMATION**

### **Replacement Parts**

Compression Lug Kit	Part Number
Hi-Tech Fuse Compression Lug	LFEK-HTH + Conductor Code
Cooper Fuse Compression Lug	LFE-CPS + Conductor Code
Chardon Fuse Compression Lug	LFE-CH + Conductor Code

Note:

Elastimold, Hi-Tech, Easton and Cooper, these brand names are property of their respective owners. All company, product and service names used in this catalog/ instruction sheet, are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.

### **CHARDON FUSES**



Table 1: Electreical Characteristics of the Elbow Fuses and Catalog Numbers

	Electrical Characteristics of the Elbow Fuses								
Voltage Class System(kV)	N o m i n a l Fuse Voltage Rating(kV)	N o m i n a l Fuse Current Rating(A)	Fuse Catalog Number	Minimum Melt l²t (A²s)	Maximum Total I <sup>2</sup> t (A <sup>2</sup> s)	Peak Arc Voltage (kV)	Maximum Continuous Current (A)		
							25°C	40°C	65°C
25 15.5	6	CHFEF155006	1410	4040	40	7.7	7.3	6.8	
		8	CHFEF155008	1565	4360	40	8.3	7.9	8.5
	45.5	10	CHFEF155010	1760	4750	40	12.9	12.3	11.5
	15.5	12	CHFEF155012	1850	5350	40	15.7	15.2	14.6
		18	CHFEF155018	1950	8750	38	23.2	22.3	21.3
		20	CHFEF155020	2120	9090	38	23.3	22.5	21.4

### Table 2: Recommended Fuse Current Ratings for Transformer

Nominal Fuse Rated Voltage				15.	5kV			
			1-Phase Vo	oltage Rating	(kV) - Phase	to Ground		
1-Phase Transformer kVA	12&1	2.47	13	3.2	13	3.8	14	4.4
	А	В	А	В	А	В	Α	В
10		6		6		6		6
15		6		6		6		6
25		6		6		6		8
37.5	6	8	6	8	6	6		6
50	8	10	8	10	8	10	8	10
75	12	12	10	12	10	12	10	1.
100	12	18	12	18	12	12	12	1.
167	20		20		20		20	

	3-Phase Voltage Rating (kV)-Phase to Phase					
3-Phase Transformer kVA	20	0.8	22.9 to 24.9			
	A	В	A	В		
75		6		6		
100	6	6		6		
112.5	6	8	6	6		
150	8	10	8	10		
225	10	12	10	12		
300	12	18	12	18		
500	20	20	18	20		

#### Note:

- (1) Fuses election is based on the continous current rating of the fuses at 40°C. Fuses in listed Column A allow between 1.4 and 2 times the rated current of the transformer; those listed in Column B, allow 2 to 3 times the rated current of the transformer.
- (2) Recommended fuses meet in rush criteria of 12 times transformer gull load current for 0.1 second and 25 times full load current for 0.01second.
- (3) Fuses meet cold load pick up criteria of 6 times transformer full load current for 1 second and 3 times full load current of 10 seconds.





CÓDIGO

35-ETP600

## PLUGUE DE REDUÇÃO - PR 35kV-600/200A



convert a standard 600A deadbreak interface deadbreak interface of to a standard 200A loadbreak interface.

The ETP is ideal for applications where a 200A tap is desired for test or ground purposes. The ETP is also ideal for adding a 200A tap to an existing 600A T-body connector. The 200A interface allows for live test, visible ground, addition of a 200A tap, or installation of an elbow arrester.

The Chardon Elbow Tap Plug (ETP) is used to The Chardon ETP meets all the requirements of IEEE standard 386, and is 200A three phase switching and three phase fault close rated. Furthermore, it incorporates an all copper current path, which provides reliable and consistent performance under all conditions

### **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 26 kV
- / AC 1 Minute Withstand -50 kV

### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **VOLTAGERATINGS**

Minimum Corona Voltage Level	26 KV
BIL and Full Wave Crest	150 MV
DC 15 Minute Withstand	103 KV
AC 1 Minute Withstand	59 KV
Max. Rating Phase to Ground	21.1 kV
Max. Bating Phase to Phase	36.6 MA
Voltage Class	35 kV

### **CURRENT RATINGS**

	Description	Amperes	
Vinda seutomatica este de tribu.	Continuous	600A rms	
600A Interface	Short Time	25,000A rms symmetrical for 0.17 s     10,000A rms symmetrical for 3.0 s	
Continuous	Continuous	200A rms	
	Switching	10 operations at 200 amps ms at 36.6 kV	
200A Interface	Fault Close	10,000A rms symmetrical at 36.6 kV for 0.17 s after 10 consecutive successful switching operations	
Short Time		10,000A rms symmetrical for 0.17s     3,500A rms symmetrical for 3.0 s	

System design and protection must recognize the ratings of 200A interface.

## DETAILED COMPOSITION OF THE CHARDON ELBOW TAP PLUG (ETP)

### /LOCKING GROOVE

Locking groove assures proper installation by "locking" into elbow.

### ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

### I FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

### / SEMICONDUCTING SHIELD

Precision molded peroxide cured semiconducting shield provides ground shield continuity and meets the requirements of IEEE Standard 592.

### HEX BROACH

5/16" hex broach permits installation with torque tool.

**600A INTERFACE** 

200A INTERFACE

### / STOP RING

Limits piston and finger contact travel during fault close.

### / DRAIN WIRE TAB

Drain wire tabs provide a convenient point to connect drain wire to ensure grounding of the connector shield.

### / INSULATION LAYER

High quality peroxide cured EPDM Insulation is mixed and formulated in-house for complete control of rubber characteristics.

### / THREADED CONNECTION TO T-BODY

5/8" – 11 UNC copper threads provided connection to T-Body connector.

### ORDERING INFORMATION

35 kV, 600A Elbow Tap Plug

35-ETP600







CÓDIGO 35-LBI200

## PLUGUE DE INSERÇÃO SIMPLES PIS - SMALL - 35kV-200A



The Chardon Bushing Insert threads onto a standard 200A bushing well. The combination of the bushing well and bushing insert perform the same function as a one piece integral loadbreak bushing, while providing the flexibility to change the bushing insert in the field, without taking the transformer or other apparatus out of service. The bushing insert and loadbreak elbows are the primary components in all ANSI/IEEE loadbreak connections.

The Chardon Bushing Insert incorporates an all copper current path. This provides reliable and consistent performance under all conditions.

The Chardon 35kV Bushing Insert meets all the requirements of IEEE Standard 386, the interface design meets interface 7B (Fig 9 in IEEE Std 386-2016) and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the bushing insert provides a fully shielded and fully submersible connection for loadbreak applications.

No special tools are required for installation. The bushing insert can be installed by hand or with the assistance of a torque tool. An internal hex broach allows for the installation by the torque tool.

### **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

/ Minimum Corona Voltage Level – 26 kV

/ AC 1 Minute Withstand - 50 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

1 Physical Inspection

I Periodic Dissection

Periodic X-ray Analysis

### **VOLTAGE RATINGS**


Voltage Class	35 kV
Max. Rating Phase to Phase	36.6 kV
Max. Rating Phase to Ground	21.1 kV
AC 1 Minute Withstand	50 kW
DC 15 Minute Withstand	103 kV
BIL and Fell Wave Crest	150 kV
Minimum Corona Voltage Level	26 kV

<sup>- 35-</sup>LBI200-190124-REV01

### **CURRENT RATINGS**

Description	Test Parameters
Continuous	200A rms
Switching	10 operations at 200A rms at 36.6 kV
Fault Close	10,000A rms symmetrical at 36.6 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	• 10,000A rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s

### DETAILED COMPOSITION OF THE CHARDON LOADBREAK BUSHING INSERT



### ORDERING INFORMATION

35 kV, 200A Loadbreak Bushing Insert

35-LBI200





CÓDIGO 🔏

35-LE200

## TERMINAL DESCONECTÁVEL COTOVELO - TDC - SMALL 35kV-200A



The Chardon Loadbreak Elbow is a fully shielded, submersible and insulated termination for connecting underground cable to transformers, switchgear, and other apparatus equipped with loadbreak bushings, junctions, or other loadbreak connectors. The bushing insert and loadbreak elbows are the primary components in all ANSI/IEEE loadbreak connections.

The Chardon 35kV Loadbreak Elbow meets all the requirements of IEEE Standard 386, the interface design meets interface 78 (Fig 9 in IEEE Std 386-2016), and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. Chardon Loadbreak Elbows are molded using high quality peroxide-cured insulating and semi-conducting EPDM rubber. All insulating rubber is compounded in house, using Chardon developed proprietary formulations.

Chardon Loadbreak Elbows include a stainless steel pulling eye. An optional capacitive test point is available. Included with the elbow kit is a bi-metal or copper compression connector, and a tin plated copper probe with an arc quenching tip.

### **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- Minimum Corona Voltage Level 26 kV
- / AC 1 Minute Withstand 50 kV
- / Test Point Voltage Test

Tests conducted in accordance with Chardon manufacturing process requirements:


- / Physical Inspection
- 1 Periodic Dissection
- Periodic X-ray Analysis

### **VOLTAGE RATINGS**


Voltage Class	35 kV
Max. Rating Phase to Phase	36.6 W
Max. Rating Phase to Ground	21.1 kV
AC 60 Hz 1 Minute Withstand	50 kV
DC 15 Minute Withstand	103 kV
BIL and Fall Wave Crest	150 kV
Minimum Corona Voltage Level	26 kV

Ravision Clate: 07/02/2024

### DETAILED COMPOSITION OF THE CHARDON 35 KV SMALL INTRFACE LOADBREAK ELBOW



### DETAILED COMPOSITION OF THE CHARDON 35 KV SMALL INTRFACE LOADBREAK ELBOW



### ORDERING INFORMATION

Chardon Loadbreak Fuse Elbow kits are packaged in a heavy duty plastic bag. Each elbow kit includes the following:

/ Silicone Grease

1 Bi-Metal or Copper Compression Connector

/ Plated Copper Probe

/ Installation Instructions Sheet

/ Probe Installation Wrench

/ Elbow

### To order a Chardon 35 kV Elbow Kit, follow the steps below:

35-LE200	"W"	"X"	"Y"	"Z"
----------	-----	-----	-----	-----

"W" = Enter T if want a Capacitive Test Point

"X" = Cable Range Code (C,D,E or F)

"Y" = Conductor Code (See table)

"Z" = Enter C if a Plated Copper Connector is Desired (Bi-metal are standard)

### 35 kV, 200A Loadbreak Cable Ranges (Insulation Diameter)

Cable Range Code	Inches	Millimeters
C	0.846 - 1.051	21.5 - 26.7
D	0.976 - 1.181	24.8 - 30.0
E	1.067 - 1.311	27.6 - 33.3
F	1.232 - 1.469	31,3 - 37,3

### Conductor Code Table

CONDUCTOR	Concentric or C	Concentric or Compressed		r Solid
CODE	AWG or kemil	mm³	AWG or kemil	mm²
01	#6	TE	#4	-
02	64	-	<b>#</b> 3	25
03	43	25	#2	35
04	<b>#</b> 2	35	<b>e1</b>	-
05	#1	E	1/0	50
06	1./0	50	2/0	70
07	2/0	70	3/0	120
08	3/0	-	4/0	95
09	4/0	95	250	120
18	250	120	300	-

Example

To order a standard Chardon 55 kV Loadbreak Elbow with a cable insulation diameter of 28 mm, a 5/0 binnetal compression connector and a capacitive test point, order the following part number: 35-LE200TD08.







CÓDIGO 35-LFE200

## TERMINAL DESCONECTÁVEL COTOVELO PORTA FUSÍVEIS 35kV-200A



The Chardon 35 kV Class Fused Loadbreak Elbow Connector combines a fully-shielded and insulated loadbreak elbow with full range current-limiting fuse protection. The Chardon Fused Loadbreak Elbow Connector provides a convenient and cost effective method to add fusing protection to underground distribution systems utilizing 200 A, 35 kV Class loadbreak bushings. Designed as a hot stick operable switching device, it is tested at the maximum fuse rating in accordance with the IEEE 386-2006 standard. The product is fully sealed and submersible.

Chardon Fused Loadbreak Elbow Connectors are molded using high quality peroxide-cured

EPDM rubber, manufactured in Chardon's facilities, under strict quality controls. Standard features include a copper probe adapter, bimetal connector, plated copper loadbreak probe and a stainless steel reinforced pullingeye. The product is designed to accept a wide range of cable conductor and insulation sizes.

Chardon Fused Loadbreak Elbow Connectors are the ONLY fused elbow connectors on the market that can accept fuses manufactured by Cooper Power Systems (Eaton) and Hi-Tech (ABB). This is accomplished by ordering the appropriate lug kit. This feature allows the customer an option which is not available on competitive products.

### **PRODUCT TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 26 kV
- # AC 1 Minute Withstand 50 kV
- I Test Point Voltage Test

Tests conducted in accordance with Chardon manufacturing process requirements:

- I Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	35 kV
Max. Rating Phase to Phase	36.6 kV
Max. Rating Phase to Ground	21.1 kV
AC 1 Minute Withstand	50 kW
DC 15 Minute Withstand	103 kV
BIL and Full Wave Crest	150 kV
Minimum Corona Voltage Level	26 kV

Revision Date: 08.07.2024

### **CURRENT RATINGS**

Description	Test Parameters
Continuous	Fuse rafing
Switching	10 operations at 200 amps rms at 36.3 kV
Fault Close	10,000 amps rms symmetrical at 36.6 kV for 0.17 s after 10 consecutive successful switching operations

### DETAILED COMPOSITION OF THE CHARDON 35 kV LOADBREAK FUSE ELBOW

### #LOADBREAK PROBE

Tin plated copper probe with arc extinguishing tip, allows for dependable switching operations.

### / PROBE ADAPTER

Designed to securely thread the loadbreak probe into its corresponding socket.

### INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated in-house for complete control of rubber characteristics.

### / BIMETAL CONNECTOR

Customized BI Metal connector designed for Chardon, CPS and HI-Tech fuse provides reliable current path.

Fig. fr Detail Chardon Fuse Elbow Composition (Chardon Fuse Installed)

### # SEMICONDUCTING INSERT

Precision molded peroxide cured semiconducting insert provides corona-free electrostatic shielding of the compression connector.

/ TEST POINT


CHARDON FUSE

#### I SEMICONDUCING SHIELD

Precision molded peroxide cured semiconducting shield provides ground shield continuity and meets IEEE standard 592.

I TEST POINT

### CHARDON 35 kV LOADBREAK FUSE ELBOW DRAWING



### ORDERING INFORMATION

Chardon Loadbreak Fuse Elbow kits are packaged in a heavy duty plastic bag. Each elbow kit includes the following:

/ Fused Elbow, Cable Housing / Hex Wrench / Fused Elbow, Elbow Housing

/ Compression Lug Kit

1 Probe

/ Silicone Grease

/ Towel

I Installation Instruction Sheet

Current-limiting fuses sold separately. See "Chardon Fuses" below for fuse recommendations, electrical satings and catalog numbers.

### To order a Chardon 35 kV Fuse Elbow Kit, follow the steps below:

35-LFE200T	"Х"	"Y"	"Z"
------------	-----	-----	-----

"X" = Enter Cable Range Code (A, B, C or D)

"Y" = If a Hi-Tech Fuse will be used in the Fused Elbow, Enter "HE". If a Cooper Fuse will be used in the Fused Elbow, enter "CP". If a Chardon Fuse will be used in the Fused Elbow, enter "CH".

"Z" = Enter Conductor Code (See Conductor Code Table Below)

Range Code	Inches	Millimeters
C	0.846 - 1.051	21.50 - 26.70
D	0.976 - 1.181	24.80 - 30.00
E	1.087 - 1.311	27.60 - 33.30
E	1.232 - 1.469	31.30 - 37.30

### Conductor Code Table

CONDUCTOR	Concentric o	r Compressed	Compa	Compact or Solid			
CODE	AWG or kemil	mm <sup>2</sup>	AWG or kemil	mm <sup>2</sup>			
01	#6		#4	(*)			
02	#4	-	- <del>P</del> 3				
03	13	25 #2		35			
04	#2	35	φį	-			
05	#1	STREET, STA	1/0	50			
06	1/0	50	2/0	70			
07	2/0	70	3/0	SWARD AND AND AND AND AND AND AND AND AND AN			
08	3/0		4/0	95			
09	4/0	95	250	120			
10	250	120	300	-			

To order a Chardon 35 kV Loadbreak Pused Elbow with a cable insulation diameter of 8.850°, using a Hi-tech fuse, and a 3/0 compression connector, order the following number: 35-LFE200T-B-HE08




### ORDERING INFORMATION

### Replacement Parts


Compression Lug Kit	Part Number
Chardon Fuse Compression Lug	LFE-CH + Conductor Code

### **CHARDON FUSES**





Voltage	Nominal	Nominal	Nominal I <sup>2</sup> t (A <sup>2</sup> s)		Peaking	Peak arc
Class System (kV)	Fuse Voltage Rating (kV)	Fuse Current Rating (A)	Pre-arc I <sup>2</sup> t	Clearing I <sup>2</sup> t	Capacity (kA)	voltage (kV)
35 23	10	400	1116	50	60	
	16	1000	2555	50	60	
	20	1680	4380	50	60	
	25	2500	6225	50	60	
	30	5390	13800	50	60	
	40	40	6240	16856	50	60
	50	10000	24900	50	60	
	60	14500	36900	50	60	



Prospective circuit current (RMS)





CÓDIGO 35-LIC200

## RECEPTÁCULO ISOLANTE BLINDADO - RIB - 35kV-200A



The Chardon Protective Cap is an accessory product to other 35 kV, 200A products with loadbreak interfaces (bushing inserts, loadbreak junctions, feed thru inserts, etc.). It is designed to physically seal and electrically insulate loadbreak bushing interfaces. When installed on a loadbreak bushing interface, and

properly grounded using the attached drain wire, the Loadbreak Protective Cap provides a submersible, fully shielded insulated cap for energized bushings.

The Loadbreak Protective Cap can be used for temporary or permanent applications.

### **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 26 kV
- / AC 1 Minute Withstand 50 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	35 kV
Max. Rating Phase to Phase	36.6 kV
Max. Rating Phase to Ground	21,1 kV
AC 1 Minute Withstand	50 lor
DC 15 Minute Withstand	103 kV
BIL and Full Wave Crest	150 kV
Minimum Corona Voltage Level	26 kV

• 95LIC200-112519-REV02

### DETAILED COMPOSITION OF THE CHARDON LOADBREAK PROTECTIVE CAP

### # PULLING EYE

Molded in stainless steel pulling eye Insures high strength for hotstick operation.

### # SEMICONDUCTING INSERT

Precision molded peroxide cured semiconducting insert provides corona-free electrostatic shielding of the connector.

### / LATCHING RING

Semiconducting molded locking ring secures cap on nose piece of mating product.

### #INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated in-house for complete control of rubber characteristics.

### / DRAIN WIRE TAB


Drain wire tab provides a convenient point to connect drain wire to ensure grounding of the connector shield. A drain wire is included with the product.

### I SEMICONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

### / PROBE

Brass probe provides reliable conductive path with mating female-contacts.



### ORDERING INFORMATION

35 kV, 200A Loadbreak Protective Cap

35-LIC200





CÓDIGO A

35-LJ200

## BARRAMENTO DE DERIVAÇÃO 35kV-200A



The Chardon 200 A, 35 kV Class Loadbreak Junction provides two, three or four 21.1/36.6 kV loadbreak interfaces that are internally bused together and meet all requirements of IEEE Standard 386<sup>TM</sup> — Separable Insulated Connector Systems. Loadbreak Junctions are used in padmounted apparatus, under-ground vaults, and other apparatus to sectionalize, establish loops, taps, or splices, and to facilitate apparatus changeouts.

Sectionalizing a cable run to find and isolate a cable fault is made easy when a loadbreak junction is used with 35 kV Class Loadbreak elbows and other accessories meeting the requirements of IEEE Standard 386<sup>TM</sup>. The Chardon Loadbreak design incorporates an all copper current carrying path, which provides reliable and consistent performance under all conditions.

The Chardon Loadbreak Junction meets all the requirements of IEEE standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386. When installed with mating components, the loadbreak junction provides a fully shielded connection for loadbreak applications.

### **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

/ Minimum Corona Voltage Level - 26 k∀

AC 1 Minute Withstand − 50 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

/ Physical Inspection

/ Periodic Dissection

/ Periodic X-ray Analysis

### **VOLTAGE RATINGS**


Minimum Corona Voltage Level	26 kV
BIL and Full Wave Crest	150 kW
DC 15 Minute Withstand	103 kV
AC 1 Minute Withstand	50 NV
Max. Rating Phase to Ground	21.1 kV
Max. Rating Phase to Phase	36.6 W
Voltage Class	35 kV

<sup>+ 35-</sup>LJ200-102220-REV01

### **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps ms
Switching	10 operations at 200 amps rms at 36.6 kV
Fault Close	10,000 amps rms symmetrical at 36.6 MV for 0.17 s after 10 consecutive successful switching operations
ShortTime	• 10,000 amps rms symmetrical for 0.17 s • 3,500 amps rms symmetrical for 3.0 s

### DETAIL COMPOSITION OF THE CHARDON LOADBREAK JUNCTION



### ORDERING INFORMATION

### Each kit contains:

- I Loadbreak Junction (with mounted bracket or straps, depending on product ordered)
- / Shipping Caps (not for energized operation)
- // Silicone Grease
- Installation Instruction Sheet

### ORDERING INFORMATION


### Loadbreak Junction Part Numbers

Part Description	Junction Only	Junction with bracket	Junction with U-Straps
35kV 200A Junction-2	35-L3200F2	35-LJ200F259	35-L9200F2U
35kV 200A Junction-3	35-LJ200F3	35-LJ200F35S	35-LJ200F3U
35kV 200A Junction-4	35-L1260F4	35-LJ200F-459	35-LJ200F4U

### Replacement Parts

Description	Catalog Number
U-Strap Kit (1 Strap)	35-LJ200U
Stainless Steel Bracket -2 way	35-LJBKTF2
Stainless Steel Bracket-3 way	35-LIBKTF3
Stainless Steel Bracket -4 way	35-LJBKTF4

### Junction with Bracket Dimensional Information



2.6" [66.7mm]

35kV	
Stacking Dimer	nsions
S7.	0.8"(21mm)
\$9	3.4*(86.5mm)
\$10	8.3°(211.6mm)
\$11 9.5"(240@mm)	
M4	See Dimensional


	Physical D	Imensions	VIII.	M4	Mounting Dir	nensions in.(	mm)				
Number of Interfaces	In. (mm)		per of Interfaces In. (mm)		Configu	raation1	Configuraation2		Configu	Configuraation3	
İ	A 8	Min.	Max.	Min.	Max	Min	Max.				
2	16.1 (410)	7.2 (184)	12.6 (320)	16,5 (420)	9.2 (233)	13.1 (333)	5.7 (146)	9.7 (246)			
3	20.1 (510)	10.9 (277)	16.5 (420)	20.5 (520)	13,1 (333)	17.0 (433)	9.7 (246)	13.6 (346)			
4	24.0 (610)	14.9 (379)	20.5 (520)	24.4 (620)	17.0 (433)	21.0 (533)	13.6 (346)	17.6 (446)			

\* Configuration 1, Both feet turned out. Configuration 2. One foot turned out, one in. Configuration 3. Both feet turned in.



enercom

### **Junction with U-straps Dimensional Information**







CÓDIGO 35-LPFT200

## PLUGUE DE BY-PASS - PBP 35kV-200A



The Chardon 200A, 35kV Class Loadbreak Portable Feed Thru is designed to be installed on a parking stand, attached to a transformer or other apparatus. Two bushing insert loadbreak interfaces can be mated with an elbow arrester, a loadbreak elbow, or an insulated cap. When mated with other products that meets IEEE Standard 386, the portable feed thru provides a fully shielded, submersible connection for loadbreak operation.

The Chardon Portable Feed Thru meets all the requirements of IEEE Standard 386, and is fully interhoangeable with competetior's products and mating products that also meet IEEE Standard 386. The indicating ring design eliminates the guesswork of loadbreak installation, it provides feedback to determine if the elbow is properly installed.

### **PRODUCTION TESTS**

#### Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 26 kV
- AC 1 Minute Withstand 50 kV

### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **VOLTAGE RATINGS**


Voltage Class	35 kV
Max. Bating Phase to Phase	36.6 kV
Max. Rating Phase to Ground	21.1 kV
AC 1 Minute Withstand	50 kV
DC 15 Minute Withstand	103 kV
BIL and Full Wave Crest	#50 kV
Minimum Corona Voltage Level	26 kV

- 35LPFT200-062123-REV01

### **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps ms
Switching	10 operations at 200 amps rms at 36.3 kV
Fault Close	10,000 amps imms symmetrical at 26.6 kV for 0.17's after 10 consecutive successful switching operations
Short Time	10,000 amps rms symmetrical for 0.17 s     3,500 amps rms symmetrical for 3.0 s

### DETAILED COMPOSITION OF THE CHARDON LOADBREAK PORTABLE FEED THRU



### / LOCKING GROOVE

Locking groove assures propera installation by "locking" into elbow.

### / FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

### / INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

### / INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated inhouse for complete control of rubber resistance.

#### / CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

### ORDERING INFORMATION


### Each Portable Feed Thru kit includes the following:

- / Portable Feed Thru
- Shipping Cap (not for energized operation)
- / Stainless Steel Bail Assembly
- I Installation Instruction Sheet

To order the 35kV Class Portable Feed Thru Kituse the P/N below:

35kV Loadbreak Portable Feed Thru

35-LPFT200







CÓDIGO 15-LEA/25-LEA/35-LEA

## TERMINAL DESCONECTÁVEL COTOVELO PARA-RAIOS 15/25/35kV-200A



The Chardon Elbow Arrester combines metal oxide varistor module in a rubber elbow to provide overvoltage system protection. The Chardon Elbow Arrester housing design meets IEEE 386 standard. It is molded with high quality peroxide-cured insulating and semi-conducting rubber and is fully interchangeable with competitors' products that also meet IEEE standard 386.

Chardon Elbow Arresters are used on underground systems in pad-mounted transformer and entry cabinets, vaults switching devices and other insulations to provide shielded deadfront arrester protection. Installing Chardon Elbow Arrester at both ends of an open point on a loop system and the end of a radial system protect equipment and extend cable life.

### PRODUCTION TEST OF ELBOW ARRESTER


- / Partial Discharge Test
- / Voltage at 1mA
- / Leakage Current
- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **PRODUCTION TEST OF MOV MODULE**

- / Partial Discharge Test
- / Voltage at 1mA
- / Leakage Current
- / Batch High-current, Short-duration test
- / Batch Thermal Stability test
- / Batch Aging test
- / Physical Inspection

#### Revision date: 11-01-2023

### DETAILED COMPOSITION OF THE CHARDON ELBOW ARRESTERS



### Table 1

Electrical Characteristics							
Duty Cycle Voltage MCOV Rating (kV) (kV)	MCOV (kV)	Equivalent Front of Wave (kV Crest)	Maximum Discharge Voltage (kV Crest) 8/20μs Current Wave				
			1.5kA	3kA	5kA	10kA	20kA
3	2.55	11.0	9.0	9.7	10.4	11.4	13.0
6	5.1	22.0	18.0	19.4	20.8	22.7	26.0
9	7.65	31.7	26.0	28.0	30.0	32.8	37.4
10	8.4	33.0	27.0	29.1	31.2	34.1	38.9
12	10.2	41.5	33.9	36.6	39.2	42.9	48.9
15	12.7	51.8	42.4	45.7	49.0	53.6	61.1
18	15.3	62.2	50.9	54.9	58.8	64.3	73.4
21	17.0	66.0	54.0	58.2	62.4	68.2	77.9
24	19.5	77.0	63.0	67.9	72.8	79.6	90.8
27	22.0	87.2	71.4	76.9	82.4	90.1	103
30	24.4	97.1	79.5	85.7	91.8	100.0	115.0
36	29.0	116.0	95.3	103.0	110.0	120.0	137.0

### Table 2

System Volt	age (kV rms)	Commonly Applied Arrester Duty-cycle(MCOV) Voltage Rating (kV rms) on Distribution System				
Nominal Voltage	Maximum Voltage Range B	4-Wire Multigrounded Neutral Wye	3-Wire Low Impedance Grounded	Delta and 3-wire High Impedance Grounded		
2.4	2.54			3(2.55)		
4.16 Y/2.40	4.40 Y/2.54	3(2,55)	6(5.1)	6(5,1)		
4.26	4.40		W	6(5.1)		
4.80	5.08	-	-	6(5.1)		
6.90	7.26	*		9(7.65)		
8.32 Y/4.80	8.80 Y/5.08	6(5.1)	9{7,65}	-		
12:00 Y/6:93	12.7 Y/7.33	9(7.65)	12(10.2)			
12.47 Y/7.20	13-20 Y/7.62	9(7,65) or 10(8.4)	15 (12.7)	-		
13.20 Y/7.62	13.97 Y/8.07	10(8.4)	15 (12.7)	0 mm 1 mm		
13.80 Y/7.97	14.52 Y/8.388	10(8.4) and 12(10.2)	15 (12.7)	-		
13.80	14.52	*	14	18(15.3)		
20.76 Y/12.00	22.00 Y/12.70	15 (12.7)	-	-		
22.86 Y/12.00	22.00 Y/12.70	15 (12.7)	12			
24.94 Y/14.40	26.40 Y/15.24	18 (15.3)	-	-		
27.60 Y/15.935	29.255 Y/1689	21 (17.0)				

### PROTECTIVE CHARACTERISTICS

The protective characteristics of the elbow arrester are shown in Table 1.

### GENERAL APPLICATION RECOMMENDATION

The rating of an arrester is the maximum power frequency line-to-ground voltage at which the arrester is designed to pass an operating duty-cycle test. Table 2 provides a general application guide for the selection of the proper arrester rating for a given system voltage and system grounding configuration as outlined in the IEEE Std C62.22 standard application guide.

To ensure that the arrester ratings will not be exceeded, CHARDON GROUP application engineers are available to make recommendations.

### PERFORMANCE TEST CHARACTERISTICS

The Elbow Arrester consistently withstands the following design test:

- / Duty Cycle Test
- / High-current, Short-duration Discharge test
- / Low-Current, Long-Duration Discharge test

# A B 2.28° (58mm)

### ORDERING INFORMATION

IEEE Std 386 Standard Interface	Duty Cycle (kV)	MCOV Rating (kV)	A (mm)	B (mm)	C (mm)	D (mm)	Catalog Numbe
	3	2.55	232	189	181	88	15-LEA3
	6	5.1	232	189	181	88	15-LEA6
	9	7.65	232	189	181	88	15-LEA9
15kV	10	8.4	232	189	181	88	15-LEA10
	12	10.2	232	189	181	88	15-LEA12
	15	12.7	232	189	181	88	15-LEA15
	18	15.3	232	189	181	88	15-LEA18
	10	8.4	232	189	195	100	25-LEA10
	12	10.2	232	189	195	100	25-LEA12
25kV	15	12.7	232	189	195	100	25-LEA15
	18	15.3	232	189	195	100	25-LEA18
	21	17.0	308	264	195	100	25-LEA21
	10	8.4	232	189	195	100	35-LEA10
	18	15.3	232	189	195	100	35-LEA18
35kV	21	17.0	308	264	195	100	35-LEA21
(Small Interface)	24	19.5	308	264	195	100	35-LEA24
	27	22.0	308	264	195	100	35-LEA27
	30	24.4	348	306	195	100	35-LEA30
	36	29.0	348	306	195	100	35-LEA36





CÓDIGO

15-SOB200 25-SOB200 35-SOB200

## PLUGUE ISOLANTE BLINDADO PIB - 15/25/35kV-200A



The Chardon Insulated Standoff Bushing, available in 15 kV, 25 kV, and 35 kV, meets the IEEE 386 standards. Made of quality peroxide-cured EPDM rubber, it provides a reliable loadbreak interface. In the field, it aids in isolating energized cables and allows both temporary and permanent parking of

loadbreak elbows aligned with IEEE 386. When mated with similarly rated products, it serves as a fully-shielded, submersible separable connector. Built with a stainless steel eyebolt and base bracket, it's suitable for mounting on the apparatus parking stand.

### **PRODUCTION TESTS**

### Tests conducted in accordance with IEEE/ANSI Standard 386:

Voltage Class	15 kV	25 kV	35 kV
Minimum Corona Voltage Level (kV rms)	11	19	26
AC 1 Minute Withstand (kV rms)	34	40	50

### Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	15 kV	25 kV	35 kV
Max. Rating Phase to Phase (kV rms)	14.4	26.3	36.6
Max. Rating Phase to Ground (kV rms)	8.3	15.2	21.1
AC 1 Minute Withstand (kV rms)	34	40	50
DC 15 Minute Withstand (kV rms)	53	78	103
BIL and Full Wave (kV crest)	95	125	150
Minimum Corona Voltage Level (kV rms)	11	19	26

### ORDERING INFORMATION

15 kV, 200A Insulated Standoff Bushing	15-SOB200
25 kV, 200A Insulated Standoff Bushing	25-SOB200
35 kV, 200A Insulated Standoff Bushing	35-SOB200

•Revision Date: 11/02/2023





CÓDIGO 35-LFTI

## PLUGUE DE INSERÇÃO DUPLO PID - 35kV-200A



The Chardon Loadbreak Feed Thru Insert threads onto a standard 200A bushing well and provides dual loadbreak bushing interfaces. It can convert radial-feed transformers to feed thru transformers and add in-line arrester protection if needed. The torque limit ratchet feature prevents the bushing well stud from breaking during installation.

The ratchet feature allows users to rotate the feed thru insert for 360° to orient the feed thru insert in the desired position. The Chardon Loadbreak Feed Thru Insert meets all the requirements of IEEE

Standard 386, and is fully interchangeable with competitor's products and mating products that also meet IEEE Standard 386.

When installed with mating components, the Feed Thru Insert provides a fully shielded and fully submersible connection for loadbreak applications.

### **PRODUCTION TESTS**

Tests conducted in accordance with IEEE/ANSI Standard 386.

- / Minimum Corona Voltage Level 26 kV
- / AC 1 Minute Withstand 50 kV

Tests conducted in accordance with Chardon manufacturing process requirements:

- / Physical Inspection
- / Periodic Dissection
- / Periodic X-ray Analysis

### **VOLTAGE RATINGS**

Voltage Class	35 kV
Max. Rating Phase to Phase	36.6 KV
Max. Rating Phase to Ground	21.1 kV
AC 1 Minute Withstand	50 kW
DC 15 Minute Withstand	103 kV
BIL and Full Wave Crest	150 kV
Minimum Corona Voltage Level	26 kV

<sup>-35-</sup>LFTI200-060223-REV03

### **CURRENT RATINGS**

Description	Test Parameters
Continuous	200 amps rins
Switching	10 operations at 200 amps rms at 36.6 kV
Fault Close	10,000 amps rms symmetrical af 36.6 kV for 0.17 s after 10 consecutive successful switching operations
Short Time	+ 10,000 amps rms symmetrical for 0.17 s + 3,500 amps rms symmetrical for 3.0 s

### DETAILED COMPOSITION OF THE CHARDON LOADBREAK FEED THRU INSERT

### I ARC SNUFFER ASSEMBLY

Arc quenching material extinguishes gas during loadbreak operations.

### #STOP RING

Limits piston and finger contact travel during fault close.

### / FINGER CONTACT

Tin plated copper contact provides a consistent current transfer during switching and fault close operations.

#### /INSULATION LAYER

High quality peroxide cured EPDM insulation is mixed and formulated in-house for complete control of rubber resistance.

#### I COPPER BUS BAR

Provide consistent current carry capability during operation.

### /LOCKING GROOVE

Locking groove assures proper installation by "locking linto elbow.

### /INDICATOR RING

Bright yellow ring provides close indication and assures a quality connection.

### / CONDUCTING SHIELD

Precision molded peroxide cured conducting shield provides ground shield continuity.

### / TORQUE-LIMITING RATCHET

The ratchet feature allows users to rotate the feedthru insert for 360° to orient the feedthru insert in the desired position and protect the stud from damaging.

13/8-16 UNC Threads

### ORDERING INFORMATION

### 35kV.200A Loadbreak Feed Thru Insert

35-LFTI


### Each kit contains:

- / Rotatable Feed Thru Insert
- / Shipping Cap (not for energized operation)
- / Stainless Steel Ball Assembly
- / Silicone Lubricant
- 1 Installation Instruction Sheet

### Replacement Part

**Bail Assembly** 

35-BAIL-LFTI





**GRUPO** 











